



info@c-bear.com
 +32 (0)11 603 208
 c-bear bicycle ceramic bearings
 cbearcycling

C-Bear Bottom Bracket Chart																
STEP 1 STEP 2 STEP 3	1. BB shell ID mm 2. BB shell WIDTH mm 3. Crankset:	Threaded						BB386	BBRight Carvelto	Pressfit30 (PF30)	PF30A Cannondale	BB30A Cannondale	BB30	PressFit BB86 (BB86/BB92)	BB90/95 Trak	
		BSA Road	BSA MTB	ITA	T45	T47 External	T47 Internal									T47A Factor/Carvelo
A= MTB AC= MTB-Cyclocross C= Cyclocross R= Race		68	73	70	82.5	68 (Road) 73 (MTB)	86 (Road) 77 (Road)	46 86.5 (Road)	46 79 (Road)	46 68 (Road) 73 (MTB)	46 73 (Road)	42 73 (Road)	42 68 (Road) 73 (MTB)	41 86.5 (Road) 92 (MTB)	37 90 (Road) 95 (MTB)	
Spindle diameter 24 mm	Shimano HTII Race Face Rotor 3D															
Spindle diameter 24-22 mm	SRAM/Truvativ GXP															
Spindle diameter 25 mm	Campagnolo UT Campagnolo EKAR															
Spindle diameter 30 mm	FSA EVO386 THM Clavicula SRM Origin															
	Rotor : 3D+3DF Rex 1/Rex 2 Inspower Aidu/Vegast/ Kapic SRAM Quarq Dzero Easton EC90 Hope FSA EVO392 g'thirteen Ingrid Cane Creek eeWings Race Face															
	FSA BB30/SRAM BB30 Cannondale Hollowgram Specialized - Fact															
Spindle diameter 28.99mm	DUB Sram RED/FORCE-RIVAL AXS Sram Eagle Sram Eagle AXS															